Data Sheet Issue 11/2014

# **AQUACER 581**

Wax emulsion based on a carnauba wax to improve the surface characteristics of aqueous seed coatings and for use as an anti-caking additive for the underwater granulation of thermoplastic synthetic materials.

# **Product Data**

#### Composition

Non-ionic emulsion of a carnauba wax

## **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Non-volatile matter: 30 %
Carrier: Water
Melting point (wax content): 85 °C
Viscosity (23 °C, D=400/s): < 50 mPa·s

pH value: 7.5

#### **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

## **Storage and Transportation**

Temperature sensitive. To be stored and transported between 5 °C and 35 °C. Mix well before use.

## **Applications**

## **Thermoplastics**

## **Special Features and Benefits**

Thermoplastic granulates (TPE, TPU, EVA) have a tendency to stick together ("cake") under pressure and heat. AQUACER 581 is used for the underwater granulation of such materials; it forms a protective coating around the granules to create non-sticky and free-flowing granulates. In contrast to the frequent practice of dusting the granulates with solid release agents (chalk, talcum), much lower quantities of AQUACER 581 are required so that the properties of the thermoplastics are not affected. This method also prevents the formation of dust during processing. If foam develops in the circulation water during underwater granulation, we recommend using BYK-023 (silicone defoamer) or BYK-016 (silicone-free defoamer) at a dose of 0.05-0.1%.

## **Recommended Levels**

0.2-5 % additive (as supplied) in the circulation water.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The additive is added directly into the circulation water.

#### **AQUACER 581**

**Data Sheet** Issue 11/2014

## **Seed coatings**

#### **Special Features and Benefits**

AQUACER 581 optimizes the wetting of the seed, increases the surface slip of the coating and therefore has an anti-blocking effect. The seed is therefore free-flowing and plantability is improved. The formation of dust is reduced due to the high abrasion resistance.

#### **Recommended Use**

The wax emulsion is recommended for aqueous seed coatings. It is used as an additive in systems with polymer binders and can also replace such binders as a film former.

#### **Recommended Levels**

10-30 % (as supplied) based on the total formulation when used in polymer binders. 70-90 % (as supplied) based on the total formulation when used as a substitute polymer binder.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The wax additive is preferably added at a low shear rate. Mix well before use.







**BYK-Chemie GmbH** O. Box 10 02 45 46462 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, AND Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives.

AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera

SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological

progress or further developments. This issue replaces all previous versions – Printed in Germany