



Data Sheet Issue 06/2015

# **BYK-1710**

Emissions-free polymer-based defoamer for aqueous, low-emission coatings and adhesives. Silicone-free and mineral oil-free. Very effective in alkyd emulsions and hybrid systems. Complies with guidelines such as, for example, AgBB in Germany and "Le Grenelle Environnement" in France.

## **Product Data**

#### Composition

**VOC-free (< 1500 ppm)** 

Mixture of hydrophobic solids and foam-destroying polymers, silicone-free

## **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.92 g/ml Active substance: 100 %

## **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

## **Storage and Transportation**

To be stored and transported at temperatures between 0 °C and 50 °C. Separation possible. Mix well before use.

# **Applications**

# **Coatings Industry**

## **Special Features and Benefits**

BYK-1710 has very good defoaming properties, especially in alkyd emulsions, hybrid systems as well as polyurethane and epoxy coatings. The additive has no or only a minor influence on recoatability and surface slip and reduces "cissing" (brush marks when recoating). The defoamer is easy to incorporate and emissions-free.

# **Recommended Use**

| Automotive coatings         |  |
|-----------------------------|--|
| Industrial coatings         |  |
| Wood and furniture coatings |  |
| Architectural coatings      |  |
| Protective coatings         |  |
| Overprint varnishes         |  |

especially recommended recommended

#### **BYK-1710**

Data Sheet Issue 06/2015

#### **Recommended Levels**

0.1-0.5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The additive can be incorporated in the millbase as well as in the letdown. Sufficiently high shear forces must be applied when used in the letdown.

#### **Adhesives & Sealants**

## **Special Features and Benefits**

BYK-1710 is a highly effective defoamer for all common dispersion adhesives, such as acrylate, polyurethane, and EVA dispersions. It prevents foam, both during production and during application. The product is free of silicones and mineral oil, and is especially recommended for VOC-free systems.

#### **Recommended Levels**

0.1-0.8% additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

# **Incorporation and Processing Instructions**

The additive can be added at any time during production. Sufficiently high shear forces must be applied.







**BYK-Chemie GmbH** P.O. Box 10 02 45 46462 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, ADISPERDAT®, LACTIMON®, NANOBYK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives.

AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera. SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological

progress or further developments. This issue replaces all previous versions – Printed in Germany