

BYK-323

Silicone-containing surface additive for solvent-borne coating systems with a slight reduction of surface tension and slight increase of surface slip. Thermostable up to 250 °C.
Good leveling with defoaming properties.

Product Data

Composition

Aralkyl-modified polymethylalkylsiloxane

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.99 g/ml

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Applications

Coatings Industry

Special Features and Benefits

The additive provides a slight reduction of the surface tension of coating systems. BYK-323 is a silicone leveling additive which has a defoaming effect/does not stabilize or only slightly stabilizes the foam depending on the polarity of the coating system. BYK-323 is thermostable up to 250 °C and does not negatively impact the intercoat adhesion. In matt coatings it is used to orientate the matting agent and in high solid systems that are difficult to matt (polyurethane/acid-curing/unsaturated polyester) its use gives optimum matting agent orientation without shining up. In flow coatings, BYK 323 stabilizes the flow curtain, and in metallic coatings it ensures consistent orientation of the aluminum pigments.

Recommended Use

The additive is particularly recommended for all solvent-borne coatings.

Recommended Levels

0.01-0.4 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be incorporated during any stage of the production process, including post-addition.

Special Note

Unlike so-called silicone oils, this additive is very user-friendly. Nevertheless, before use it should be determined in a series of tests whether foam is stabilized in certain systems. Similarly, the recoatability and cratering should be checked.

BYK-323

Data Sheet
Issue 10/2012

BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735
info@byk.com
www.byk.com/additives

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

This issue replaces all previous versions – Printed in Germany