Data Sheet Issue 09/2012

BYK-390

Surface additive on polyacrylate basis for solvent-borne systems. Prevents boiling marks in baking systems and has an air-releasing effect.

Product Data

Composition

Solution of a polyacrylate

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.90 g/ml Non-volatile matter (60 min, 105 °C): 50 % Solvents: Xylene Flash point: 27 °C

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

To be stored and transported at a temperature below 40 °C.

Special Note

It is recommended to pre-dilute the additive with solvents that contain aromatics.

BYK-Chemie GmbH P.O. Box 10 02 45 46462 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, JUSPERBYK®, AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

above-mentioned statements

from this fact for individual cases.
This issue replaces all previous versions – Printed in Germany