

Lab Product Data Sheet

BYK LP-R 22274

Stand : 03/2013

Composition

BYK LP-R 22274	Blend containing carboxylic acid esters and wetting and dispersing component
-----------------------	------------------------------------------------------------------------------

Typical Properties

Density at 20 °C	0,879 g/cm ³
Flash point	>140 °C
Solidification point	<-13 °C
Refractive index	1,4568

Values indicated in this data sheet describe typical properties and do not constitute specification limits

Recommended Levels

% additive (as supplied) based upon formulation	1 - 7.5 in special cases up to 10
--------------------------------------------------------	-----------------------------------

Special Hints

Incorporation and Processing Instructions

The additive can be added during the production of the plastisol or shortly before processing.

Applications

- PVC Plastisols
- highly filled
 - low/unfilled
 - foamed
 - pigmented

This additive is a test product and only on request commercially available

ANTI-TERRA®, ATEPAS®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, DISPERBYK®, DISPERPLAST®, ISAROL®, LACTIMON®, NANOBYK®, SCONA®, SILBYK® and VISCOBYK® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER® and MINERPOL® are registered trademarks of BYK-Cera.

This information is given to the best of our knowledge. Because of the multitude of formulations, production and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

This issue replaces all previous versions - Printed in Germany