

DISPERBYK-2061

VOC-free wetting and dispersing additive for aqueous and glycol-containing organic pigment concentrates to color aqueous and solvent-borne architectural coatings.

Product Data

Composition

Block copolymer with pigment affinic groups

VOC-free (< 1500 ppm)
APEO-free

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Amine value: 3 mg KOH/g
Active substance: 100 %
Density (20 °C): 1.08 g/ml

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.





Applications

Coatings Industry

Special Features and Benefits

Using DISPERBYK-2061, aqueous and glycol-containing pigment concentrates can be produced. The additive is particularly suitable for organic pigments and carbon blacks. These pigment concentrates are used as binder-free universal colorants to color aqueous and solvent-borne coating systems, predominantly for the architectural coatings field. The pigment concentrates based on DISPERBYK-2061 display a broad compatibility in the most diverse coating systems. These include aqueous alkyd resins or alkyd resin emulsions, acrylate, vinyl acetate, siloxane resin and polyurethane dispersions (blends, e.g. alkyd/polyurethane), and solvent-borne long oil alkyd coatings, even those that are aromatic-free and high solids, and thermoplastic acrylic resin systems (TPA). In addition to exceptional color strength and excellent rub-out properties, pigment concentrates with DISPERBYK-2061 display no negative influence on the coating viscosity or the drying behavior. The additive is VOC-free and contains no alkylphenol ethoxylates.

Recommended Use

Aqueous VOC-free universal colorants	
Aqueous glycol-based universal colorants	
Aqueous pigment concentrates	
Aqueous coatings	

 especially recommended  recommended

Recommended Levels

10-40 % additive (as supplied) based on organic pigments.

20-50 % additive (as supplied) based on carbon blacks.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

For optimum performance, the additive must be incorporated into the millbase before the addition of pigments. Simply pre-mix the water and additive. In all cases, only add the pigments when the additive has been thoroughly distributed.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYK®, PAPERBYK®, SCONA®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAC®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany