

# DISPERBYK-2080

Wetting and dispersing additive to stabilize titanium dioxide, inorganic pigments and fillers in aqueous coating systems without negatively impacting the water, corrosion or stain resistance. Particularly recommended for use in aqueous anti-corrosive primers and direct-to-metal systems as well as aqueous wood and furniture coatings.

## Product Data

### Composition

Solution of a copolymer with pigment-affinic groups

### Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 1.04 g/ml

Active substance: 30 %

Solvents: Water

### Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit [www.byk.com](http://www.byk.com) for further information.

### Storage and Transportation

To be stored and transported between 5 °C and 40 °C.

## Applications

### Coatings Industry

#### Special Features and Benefits

DISPERBYK-2080 uses electrosteric stabilization to deflocculate the pigments. The deflocculating property of the additive results in increased gloss and a reduced millbase viscosity. As a result of its hydrophobic nature, the additive minimizes water absorption in the entire coating system, which has a positive effect on the corrosion and stain resistance. DISPERBYK-2080 is particularly suitable for use in aqueous anti-corrosive primers and direct-to-metal systems in which it positively influences the wet and dry adhesion. It is also recommended for aqueous wood and furniture coatings.

## Recommended Use

Protective coatings	<input checked="" type="checkbox"/>
Wood and furniture coatings	<input checked="" type="checkbox"/>
Architectural coatings	<input checked="" type="checkbox"/>
Industrial coatings	<input checked="" type="checkbox"/>
Automotive coatings	<input type="checkbox"/>

☒ especially recommended    ☐ recommended

## Recommended Levels

Amount of additive (as supplied) based upon pigment:

Fillers and anti-corrosive pigments:    3-6 %  
Inorganic pigments:                        10-27 %  
Titanium dioxides:                          3-6 %

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## Incorporation and Processing Instructions

For optimum performance, the additive must be incorporated into the millbase before the addition of pigments. Simply pre-mix the water and additive. In all cases, only add the pigments when the additive has been thoroughly distributed.



Additive Guide



**BYK-Chemie GmbH**  
P.O. Box 10 02 45  
46462 Wesel  
Germany  
Tel +49 281 670-0  
Fax +49 281 65735

[info@byk.com](mailto:info@byk.com)  
[www.byk.com](http://www.byk.com)

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYPK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, PRIEX®, PURE THIX®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany