

# OPTIBENT-NT 10

High-quality, powdered rheology additive based on an activated phyllosilicate for aqueous, hydraulically hardening binder systems. Improves processability and can achieve a slightly hydrophobic effect.

## Product Data

### Composition

Modified phyllosilicate

### Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Bulk density: 300-500 kg/m<sup>3</sup>  
Moisture content: max. 8 %  
Supplied as: free-flowing, gray powder

### Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit [www.byk.com](http://www.byk.com) for further information.

### Storage and Transportation

The product is slightly hygroscopic and should be transported and stored dry in the unopened original container at temperatures between 0 °C and 30 °C.

## Applications

### Construction industry

#### Special Features and Benefits

OPTIBENT-NT 10 significantly improves the processing properties and the anti-sagging properties. The product can also reduce the water absorption of hydraulically hardened systems. Compared with other additives with a hydrophobic effect, OPTIBENT-NT 10 can be easily incorporated with low-dusting.

#### Recommended Use

OPTIBENT-NT 10 is suitable for aqueous cementitious binder systems with a fine particle size distribution.

Jointing compounds	<input checked="" type="checkbox"/>
Cementitious base coats	<input type="checkbox"/>
Thin-layered plasters	<input checked="" type="checkbox"/>

☒ especially recommended    ☐ recommended

### Recommended Levels

0.2-1.0 % additive (as supplied) based upon the total formulation, depending on the properties of the formulation to be achieved.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

### Incorporation and Processing Instructions

OPTIBENT-NT 10 is hydrophilic and can be added as supplied to the dry mix mortar formulation.

### Special Note

OPTIBENT-NT 10 is a rheology additive and not a hydrophobic agent in the conventional sense. However, as a result of its rheological properties, it enables within limits a reduction of organic thickeners, and its platelet-shaped structure can also reduce water absorption of hydrated systems.

Not suitable for plaster-based systems.



Additive Guide



**BYK-Chemie GmbH**  
P.O. Box 10 02 45  
46462 Wesel  
Germany  
Tel +49 281 670-0  
Fax +49 281 65735

[info@byk.com](mailto:info@byk.com)  
[www.byk.com](http://www.byk.com)

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYPK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, PRIEX®, PURE THIX®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany