

OPTIFLO H3300 VF

Product Data

Special Features and Benefits

OPTIFLO H3300 VF is a VOC-free polymer solution used to generate low shear viscosity. It is an aqueous solution of a hydrophobically modified nonionic polymer commonly called an associative thickener.

The use of OPTIFLO H3300 VF will increase body by generating low shear viscosity with some impact on high shear viscosity.

Recommended Use

OPTIFLO H3300 VF is designed to thicken dispersion (latex) paints. It may be used with acrylic, styrene/acrylic, and vinyl acetate copolymer latexes.

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

% Active:	17.5 %
Solvent:	NA
Appearance:	Cloudy solution
Solution viscosity:	1.000-7.000 cPs @ 25 °C
Density:	1.03 g/ml @ 25 °C (8.62 lbs/gal)
pH:	7 to 10

Recommended Levels

OPTIFLO H3300 VF is typically used at 8.0-25.0 wet pounds per 100 gallons of the final formula, but the amount required will depend upon the specific formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com/additives

ACTAL®, ADJUST-4®, ADVITROL®, BENTOLITE®, CLAYTONE®, CLOISITE®, COPISIL®, FULACOLOR®, FULCAT®, FULGEL®, FULMONT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PERMONT®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, SCP®, TIXOGEL®, Y25® are registered trademarks of BYK Additives.

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYPK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAX®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

This issue replaces all previous versions – Printed in Germany