

BYK-P 4102

Processing additive for thermoplastics (compounds and masterbatches based on PE and PP) to improve the dispersion of pigments and mineral fillers. Improves the throughput and reduces the viscosity and filter pressure value

Product Data

Composition

Low-emission combination of carboxylic acid derivatives with wetting agent properties

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Bulk density: 270 kg/m³

Drop point: > 75 °C

Supplied as: Powder

Food Contact Legal Status

The additive is suitable for applications that come into contact with food. For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

Temperature sensitive. To be stored and transported at a temperature below 50 °C.

Applications

Thermoplastics

Special Features and Benefits

BYK-P 4102 adsorbs on the surface of the fillers and pigments, therefore bringing about an optimum processing and dispersion during extrusion. It improves the torque build-up, throughput, viscosity (MVR), filter pressure value (FPV) and dispersion quality.

Recommended Use

The additive is particularly recommended for filled thermoplastic compounds and color masterbatches based on PE and PP, but also for ABS, PA and PVC.

Recommended Levels

Amount of additive (as supplied) based upon:

Mineral fillers: 0.25-2 %

Inorganic pigments: 3-15 %

Organic pigments: 10-30 %

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The product can be added to the fillers, pigments or the polymer both during or prior to compounding.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera. SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany