Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129 Revision Date: 28.01.2015

Replaces version from: 28.02.2012

Version: 1 /en Print date: 07.10.2016

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name FQ 3511 SILBER FOLCO FOAMCOAT FQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses printing ink

1.3 Details of the supplier of the safety data sheet

Address Follmann GmbH & Co. KG

> Postfach 12 63 D-32372 Minden

Telephone: +49 (571) 93 39 -0 FAX: +49 (571) 93 39 -300

Responsible Department Environmental Department +49 (571) 9339-176

E-mail (competent person) sicherheitsdatenblatt@follmann.de

1.4 Emergency telephone number

Emergency telephone number Outside USA: -001 703 527 3887 (D813)

#### SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

This product is classified as not hazardous according to regulation (EC)

1272/2008 [CLP].

Classification according to Directive

67/548/EEC / 1999/45/EEC

This product is not classified as dangerous according to 67/548/EEC /

1999/45/EEC.

2.2 Label elements

No. 1272/2008 [CLP]

Labelling according to Regulation (EC) The product does not have to be labelled according to Regulation (EC) No.

1272/2008 [CLP].

Further information EUH208: Enthält 1,2-benzisothiazol-3(2H)-one;5-chlorine-2-methyl-2,3-

> dihydro-isothiazol-3-on [26172-55-4] und 2-Methyl-2,3-dihydroisothiazol-3-on [2682-20-4] Gemisch im Verhältnis 3: 1. Kann allergische Reaktio-

nen hervorrufen.

EUH210: Sicherheitsdatenblatt auf Anfrage erhältlich.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixture

Chemical characterization Modification on basis of vinyl acetate-copolymer dispersion

# Hazardous ingredients

Ingredient		Classification (EEC) No 67/548	Concentration
		Classification (EC) 1272/2008	
and isobutane	CAS No. : 75-28-5	F+; R12	0.1 - 1.0 % by
	EC-No.: 200-857-2 Index-No.: 601-004-00-0	Flam. Gas 1; H220 Press. Gas; H220	weight
1,2-benzisothiazol-3(2H)-	CAS No. : 2634-33-5	Xn; R22 Xi; R38-41 R43 N; R50	< 0.01 % by
one	EC-No.: 220-120-9 Index-No.: 613-088-00-6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	weight

Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129



Revision Date: 28.01.2015 Replaces version from: 28.02.2012 Print date: 07.10.2016 Version: 1 /en

Ingredient		Classification (EC) No 67/548	Concentration
mixture of: 5-chloro-2- methyl-4-isothia- zolin-3-one [EC no. 247-500-7]; and 2- methyl-2H-isoth- iazol-3-one [EC no. 220-239-6] (3:1)	CAS No. : 55965-84-9 2682-20-4 26172-55-4 Index-No. : 613-167-00-5	Classification (EC) 1272/2008  T; R23/24/25 C; R34 R43 N; R50-53  Acute Tox. 3; H301 Acute Tox. 3; H311  Acute Tox. 3; H331 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0.01 % by weight

#### SECTION 4: First aid measures

## 4.1 Description of first aid measures

General advice Move out of dangerous area. Take off all contaminated clothing immediately.

Do not leave the victim unattended. Show this safety data sheet to the doctor

in attendance.

In case of skin contact Wash off immediately with soap and plenty of water while removing all con-

taminated clothes and shoes. If skin irritation occurs, seek medical advice/at-

tention.

In case of eye contact In the case of contact with eyes, rinse immediately with plenty of water and

seek medical advice.

If swallowed Rinse mouth.Do NOT induce vomiting.Call a physician immediately.

## SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), Foam, Water spray, Dry powder

Extinguishing media which must not High volume water jet

be used for safety reasons

## 5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Hazardous decomposition products formed under fire conditions. Exposure

to decomposition products may be a hazard to health.

#### 5.3 Advice for firefighters

Special protective equipment for

firefighting

In the event of fire, wear self-contained breathing apparatus.

Additional information on firefight-

ing

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from fire fighting to

enter drains or water courses.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

#### 6.2 Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface

water or sanitary sewer system. Avoid subsoil penetration.

#### 6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, uni-Methods for cleaning up

versal binder, sawdust). Clean contaminated surface thoroughly.

Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129 Revision Date: 28.01.2015

Replaces version from: 28.02.2012

Version : 1 /en Print date : 07.10.2016

Treat recovered material as described in the section "Disposal considera-

tions".

6.4 Reference to other sections

Reference to other sections Disposal considerations See also section 13

### SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Handle and open container with care. Avoid contact with skin and eyes.

None under normal processing.

Precautions Smoking, eating and drinking should be prohibited in the application area.

For personal protection see section 8. Observe label precautions.

Advice on protection against fire

and explosion

No special protective measures against fire required.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

quirements

Keep in properly labelled containers. Containers which are opened must be

carefully resealed and kept upright to prevent leakage.

Storage specifications Protect from frost.

TRGS 510 12

Recommended storage temperature 5-20 °C

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

8.2 Exposure controls

exceeded and/or in case of product release (dust).

Note: Should no job-related limit values are indicated, the product, which a monitoring exposure limit is allocated, do not contains ingredients in relevant

concentrations.

Hand protection Protective gloves complying with EN 374.Please observe the instructions re-

garding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and

the contact time.

Unsuitable material: woven fabric, Leather gloves

Suitable material : Nitriles

Eye protection Tightly fitting safety goggles

Skin and body protection Wear suitable protective equipment. Long sleeved clothing

General protective and hygiene

measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. Use protective skin cream before handling the

product. Avoid contact with the skin and the eyes.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state liquid

Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129 Revision Date: 28.01.2015

Version: 1 /en

Replaces version from: 28.02.2012

Print date: 07.10.2016

Form Liquid Colour silver

Odour characteristic Melting point [°C] / Freezing point approx. 0 °C

[°C]

Boiling point [°C] approx. 100 °C Evaporation rate [kg/(s\*m²)] not determined

Vapour pressure [kPa] 123 hPa 50 °C Temperature:

Vapour density not determined

Density [g/cm<sup>3</sup>] approx.  $1,0 - 1,2 \text{ g/cm}^3$ 

> 20 °C Temperature:

Water solubility [g/l]

Remarks: miscible

Partition coefficient n-octanol /wa-

ter (log P O/W)

not determined

Autoignition temperature [°C] not determined

Viscosity, dynamic [kg/(m\*s)] approx. 35 - 45 dPa\*s

> Temperature: 20 °C

Measuring method: Haake-Viscotester

**Explosive properties** Not relevant Oxidising properties Not relevant

## **SECTION 10: Stability and reactivity**

10.4 Conditions to avoid

Conditions to avoid None under normal processing.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Hazardous ingredients

#### 1,2-BENZISOTHIAZOL-3(2H)-ONE

Oral toxicity [mg/kg]	Test criterion	Test species	Source
1193 mg/kg	LD50	rat	100

Source: 100 - Firmendaten

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
4115 mg/kg	LD50	rat	100

Source: 100 - Firmendaten

Irritant effect on skin Skin irritation


Irritant effect on eyes Risk of serious damage to eyes.

Sensitization May cause sensitization by skin contact.

Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129 Revision Date: 28.01.2015

Version: 1 /en



Replaces version from : 28.02.2012 Print date : 07.10.2016

Carcinogenic effects no data available

Mutagenicity no data available

Reproduction toxicity no data available

# GEMISCH AUS 5-CHLOR-2-METHYL-2H-ISOTHIAZOL-3-ON UND 2-METHYL-2H-ISOTHIAZOL-3-ON

(3:1)

Oral toxicity [mg/kg]	Test criterion	Test species	Measuring method	Source
2131 mg/kg	LD50	rat	OECD Test Guideline	100
			401	

Source: 100 - Firmendaten

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
660 mg/kg	LD50	rabbit	100

Source: 100 - Firmendaten

Inhalative toxicity [mg/	Test criterion	Test species	Exposure duration	Source
1]				
0,33 mg/l	LC50	rat	4 hours	100

Source: 100 - Firmendaten

Irritant effect on skin corrosive effects

Test species rabbit
Irritant effect on eyes irritating
Test species rabbit

Sensitization Causes sensitization.

Test species guinea pig

### 11.2 Additional information

Other information (chapter 11.) No toxicology information is available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

### Hazardous ingredients

# 1,2-BENZISOTHIAZOL-3(2H)-ONE

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
2,18 mg/l	LC50	Oncorhynchus mykiss	96h	72
		(rainbow trout)		

Source: 72 - Verordnung (EG) Nr. 1272/2008 des Europäischen Parlaments und des Rates vom 16. Dezember 2008 über die Einstufung Kennzeichnung und Verpackung von Stoffen und Gemischen (Tab. 3.1)

Toxicity to daphnia	Test criterion	Test species	Exposure duration	Source
[mg/l]				
2,94 mg/l	EC 50	Daphnia magna (Water	48 h	100
		flea)		

Source: 100 - Firmendaten

Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129



Revision Date: 28.01.2015 Replaces version from: 28.02.2012 Print date: 07.10.2016 Version: 1 /en

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Source
0,11 mg/l	ErC50	Pseudokirchneriella	72 h	100
		subcapitata		

Source: 100 - Firmendaten

#### GEMISCH AUS 5-CHLOR-2-METHYL-2H-ISOTHIAZOL-3-ON UND 2-METHYL-2H-ISOTHIAZOL-3-ON (3:1)

Toxicity to fish [mg/l]	Source
0,28 mg/l	100

Source: 100 - Firmendaten

Toxicity to daphnia [mg/l]	Source
0,16 mg/l	100

Source: 100 - Firmendaten

#### 12.5 Results of PBT and vPvB assessment

Results of PBT characteristics deter-

mination

This preparation contains no substance considered to be persistent, bioaccu-

mulating nor toxic (PBT).

12.6 Other adverse effects

Further information on ecology We have no quantitative data concerning the ecological effects of this prod-

### **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Disposal considerations According to the European Waste Catalogue, Waste Codes are not product

specific, but application specific. The following Waste Codes are only sugges-

tions:

08 01 12: waste paint and varnish other than those mentioned in 08 01 11 Waste Code

08 03 13: waste ink other than those mentioned in 08 03 12

Uncleaned empty packaging

## **SECTION 14: Transport information**

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.2 Description of the	Non dangerous good	Kein Gefahrgut nach IMDG	Kein Gefahrgut nach IATA
goods			
14.2 UN proper shipping		Non dangerous good	Non dangerous good
name			

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to An-Not relevant nex II of MARPOL73/78 and the IBC Code

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations Additionally, observe any national regulations!

Commercial Product Name: FQ 3511 SILBER FOLCO FOAMCOAT FQ

Article-No.: 15290-129 Revision Date: 28.01.2015

Version: 1 /en



Replaces version from : 28.02.2012 Print date : 07.10.2016

**SECTION 16: Other information** 

Relevant R-phrases R12: Extremely flammable.

R22: Harmful if swallowed.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R34: Causes burns. R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50: Very toxic to aquatic organisms.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse ef-

fects in the aquatic environment.

Relevant H-phrases EUH208: Contains 1,2-benzisothiazol-3(2H)-one;5-chlorine-2-methyl-2,3-

dihydro-isothiazol-3-on [26172-55-4] und 2-Methyl-2,3-dihydroisothiazol-3-on [2682-20-4] Gemisch im Verhältnis 3: 1. May produce an allergic

reaction.

EUH210: Safety data sheet available on request.

H220: Extremely flammable gas. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H331: Toxic if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Wording of the hazard classes Flam. Gas: Flammable gas

Press. Gas: Gases under pressure

Acute Tox.: Acute toxicity Skin Irrit.: Skin irritation Eye Dam.: Serious eye damage Skin Sens.: Skin sensitization

Aguatic Acute: Hazardous to the aguatic environment

Skin Corr.: Skin corrosion

Aquatic Chronic: Hazardous to the aquatic environment

Department issuing safety data

sheet

**Environmental Department** 

Further information Full text of R-phrases referred to under sections 2 and 3

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.