

1.1 Product identifier		
Commercial Product Name	FTD 9073 LV Binder	
1.2 Relevant identified uses of the	e substance or mixture and uses advised against	
Relevant identified uses	printing ink	
1.3 Details of the supplier of the safety data sheet		
Address	Follmann GmbH & Co. KG Postfach 12 63 D-32372 Minden Telephone : +49 (571) 93 39 -0 FAX : +49 (571) 93 39 -300	
Responsible Department	Environmental Department +49 (571) 9339-176	
E-mail (competent person)	sicherheitsdatenblatt@follmann.de	
1.4 Emergency telephone number		
Emergency telephone number	Outside USA: -001 703 527 3887 (D813)	
SECTION 2: Hazards identifi	cation	
2.1 Classification of the substance	e or mixture	
Classification according to Regula- tion (EC) No. 1272/2008	This product is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].	
2.2 Label elements		
<b>2.2 Label elements</b> Labelling according to Regulation (E No. 1272/2008 [CLP]	C) The product does not have to be labelled according to Regulation (EC) No. 1272/2008 [CLP].	
Labelling according to Regulation (E	The product does not have to be labelled according to Regulation (Ee) not	

### SECTION 3: Composition/information on ingredients

Acrylat

#### 3.2 Mixture

Chemical characterization

## Hazardous ingredients

Ingredient		Classification (EC) 1272/2008	Concentration
1,2-benzisothiazol-3(2H)- one	CAS No. : 2634-33-5 EC-No. : 220-120-9 Index-No. : 613-088-00-6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0.01 % by weight
mixture of: 5-chloro-2- methyl-4-isothia- zolin-3-one [EC no. 247-500-7]; and 2- methyl-2H-isoth- iazol-3-one [EC no. 220-239-6] (3:1)	CAS No. : 55965-84-9 2682-20-4 26172-55-4 Index-No. : 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0.01 % by weight



### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	Move out of dangerous area.Take off all contaminated clothing immediately. Do not leave the victim unattended.Show this safety data sheet to the doctor in attendance.
In case of skin contact	Wash off immediately with soap and plenty of water while removing all con- taminated clothes and shoes. If skin irritation occurs, seek medical advice/at- tention.
In case of eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	Rinse mouth.Do NOT induce vomiting.Call a physician immediately.

### SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO2), Foam, Water spray, Dry powder
Extinguishing media which must not be used for safety reasons	High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases	Hazardous decomposition products formed under fire conditions. Exposure to decomposition products may be a hazard to health.
<b>5.3 Advice for firefighters</b> Special protective equipment for firefighting	In the event of fire, wear self-contained breathing apparatus.
Additional information on firefight- ing	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.Do not allow run-off from fire fighting to enter drains or water courses. The product itself does not burn.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective	ersonal precautions, protective equipment and emergency procedures	
Personal precautions	Use personal protective equipment.	
6.2 Environmental precautions		
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.	
6.3 Methods and material for contair	iment and cleaning up	
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean contaminated surface thoroughly.	
6.5 Additional information		
Other information	Treat recovered material as described in the section "Disposal considera- tions".	



### SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling	Handle and open container with care. Avoid contact with skin and eyes.
Precautions	Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Observe label precautions.
Advice on protection against fire and explosion	No special protective measures against fire required.

### 7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re- quirements	Keep in properly labelled containers.Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Storage specifications	Protect from frost.
TRGS 510	12
Recommended storage temperature	5 – 25 °C

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

### 8.2 Exposure controls

0.2 Exposure controls	
Respiratory protection	Note: Should no job-related limit values are indicated, the product, which a monitoring exposure limit is allocated, do not contains ingredients in relevant concentrations. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Hand protection	Protective gloves complying with EN 374.Please observe the instructions re- garding permeability and breakthrough time which are provided by the sup- plier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Suitable material :	Nitriles
Unsuitable material :	woven fabric, Leather gloves
Eye protection	Tightly fitting safety goggles
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. Use protective skin cream before handling the

product. Avoid contact with the skin and the eyes.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	Liquid
Colour	milky
Odour	characteristic
рН	7 – 9



Melting point [°C] / Freezing point [°C]	ca.0 °C
Boiling point [°C]	approx. 100 °C
Evaporation rate [kg/(s*m²)]	not determined
Vapour pressure [kPa]	123 hPa
Temperature :	50 °C
Vapour density	not determined
Density [g/cm <sup>3</sup> ]	0,9 – 1,2 g/cm <sup>3</sup>
Water solubility [g/l]	
Remarks :	miscible
Partition coefficient n-octanol /wa- ter (log P O/W)	not determined
Autoignition temperature [°C]	not determined
Explosive properties	Not relevant
Oxidising properties	Not relevant
9.2 Other information	
Flow time [s]	40 - 50 sec
Temperature :	20 °C
Measuring method :	DIN cup 4 mm

### **SECTION 10: Stability and reactivity**

### 10.4 Conditions to avoid

Conditions to avoid

None under normal processing.

# SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

### Hazardous ingredients

#### 1,2-BENZISOTHIAZOL-3(2H)-ONE

Oral toxicity [mg/kg]	Test criterion	Test species	Source
1193 mg/kg	LD50	rat	100

Source : 100 - Firmendaten	
----------------------------	--

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
4115 mg/kg	LD50	rat	100

Source : 100 - Firmendaten

Skin irritation
Risk of serious damage to eyes.
May cause sensitization by skin contact.
no data available
no data available
no data available



Oral toxicity [mg/kg]	Test criterion	Test species		Measuring method	Source
2131 mg/kg	LD50	rat		OECD Test Guideline 401	100
Source : 100 – Firmendaten					
Dermal toxicity [mg/kg]	Test criterio	on	Test sp	ecies	Source
660 mg/kg	LD50		rabbit		100
]	Test criterion	Test species		Exposure duration	Source
I]	Test criterion LC50	Test species rat		Exposure duration 4 hours	Source
I] 0,33 mg/I Source : 100 - Firmendaten	LC50	rat			
I] 0,33 mg/I Source : 100 - Firmendaten Irritant effect on skin	LC50 corrosive eff	rat			
I] 0,33 mg/I Source : 100 - Firmendaten	LC50	rat			
0,33 mg/l Source : 100 - Firmendaten Irritant effect on skin	LC50 corrosive eff	rat			Source

Test species	rabbit
Sensitization	Causes sensitization.
Test species	guinea pig

#### 11.2 Additional information

Other information (chapter 11.)

No toxicology information is available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Hazardous ingredients

#### 1,2-BENZISOTHIAZOL-3(2H)-ONE

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
2,18 mg/l		, ,	96h	72
		(rainbow trout)		

Source : 72 – Verordnung (EG) Nr. 1272/2008 des Europäischen Parlaments und des Rates vom 16. Dezember 2008 über die Einstufung Kennzeichnung und Verpackung von Stoffen und Gemischen (Tab. 3.1)

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
2,94 mg/l	EC 50	Daphnia magna (Water flea)	48 h	100

Source : 100 - Firmendaten

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Source
0,11 mg/l	ErC50	Pseudokirchneriella	72 h	100
		subcapitata		

Source : 100 - Firmendaten



GEMISCH AUS 5-CHLOR-2-M	IETHYL-2H-ISOTHIAZOL-3-ON UND 2-METHYL-2H-ISOTHIAZO	L-3-ON
(3:1)		
Toxicity to fish [mg/l]		Source
0,28 mg/l		100
Source : 100 - Firmendaten		
Toxicity to daphnia [mg/l]		Source
0,16 mg/l		100
Source : 100 - Firmendaten		
12.5 Results of PBT and vPvB assess	sment	
Results of PBT characteristics deter- mination	This preparation contains no substance considered to be persisten mulating nor toxic (PBT).	ıt, bioaccu-
12.6 Other adverse effects		
Further information on ecology	We have no quantitative data concerning the ecological effects of t uct.	his prod-
SECTION 13: Disposal conside	erations	
13.1 Waste treatment methods		
Disposal considerations	According to the European Waste Catalogue, Waste Codes are not specific, but application specific. The following Waste Codes are or tions:	•

Uncleaned empty packaging

Waste Code

### **SECTION 14: Transport information**

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.2 Description of the	Non dangerous good	Non dangerous good IATA	Non dangerous good IATA
goods			
14.2 UN proper shipping		Non dangerous good	Non dangerous good
name			

08 01 12: waste paint and varnish other than those mentioned in 08 01 11

08 03 13: waste ink other than those mentioned in 08 03 12

#### 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Additional regulationsAdditionally, observe any national regulations!

### SECTION 16: Other information

Relevant H-phrases	EUH208: Contains 1,2-benzisothiazol-3(2H)-one; mixture of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H-isothia- zol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. EUH210: Safety data sheet available on request. H301: Toxic if swallowed.

Safety Data Sheet as per Commercial Product Name : FTD 90 Article-No. : E21000136	regulation (EC) 1907/2006 FOLMANN
Revision Date : 02.09.2015	Replaces version from : 02.09.201
Version : 1 /en	Print date : 02.11.201
	<ul> <li>H302: Harmful if swallowed.</li> <li>H311: Toxic in contact with skin.</li> <li>H314: Causes severe skin burns and eye damage.</li> <li>H315: Causes skin irritation.</li> <li>H317: May cause an allergic skin reaction.</li> <li>H318: Causes serious eye damage.</li> <li>H331: Toxic if inhaled.</li> <li>H400: Very toxic to aquatic life.</li> <li>H410: Very toxic to aquatic life with long lasting effects.</li> <li>H411: Toxic to aquatic life with long lasting effects.</li> </ul>
Wording of the hazard classes	Acute Tox.: Acute toxicity Skin Irrit.: Skin irritation Eye Dam.: Serious eye damage Skin Sens.: Skin sensitization Aquatic Acute: Hazardous to the aquatic environment Aquatic Chronic: Hazardous to the aquatic environment Skin Corr.: Skin corrosion
Department issuing safety data sheet	Environmental Department

Further information

Full text of R-phrases referred to under sections 2 and 3

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.